

Audurra™ Flex Foam Disc**SANDING****Description:**

The Audurra Flex Foam Discs are engineered with a proprietary stearate coating and a flexible foam backing, these abrasives provide excellent surface contact on contoured areas, minimizing the risk of deep scratches and ensuring uniform pressure distribution. The optimized multi-hole configuration enhances dust extraction, significantly reducing clogging and swirl marks, and making the product suitable for both wet and dry sanding applications.

**Features:**

- Superior Flexibility
- Anti-clogging
- Wet or Dry Use
- User-Friendly
- Suitable for use by hand or machine

Available in:

Description	Article number	Grit	Diameter	Packaging unit
Audurra Flex Foam Discs	D15419909	P600	Ø 150 mm	10 discs = 1 box
	D15419910	P800	Ø 150 mm	10 discs = 1 box
	D15419911	P1000	Ø 150 mm	10 discs = 1 box

Audurra™ Flex Foam Disc

SANDING

Product profile:

Grain:	Premium Aluminum Oxide
Grit range:	P600 - P1000
Backing:	Film, Sponge with Grip
Coating:	Semi-Close with Stearate Coating
Bonding:	Resin over Resin

Applications:

Automotive



Aerospace



Marine



Wood



Storage:

It is recommended that all Coated Abrasive Products should be stored at constant levels of temperature and humidity within the ranges of 18-22 °C, 50-65 % RH. They should be kept away from damp (or cold) walls, windows or floors to avoid possible moisture absorption. Equally storage adjacent to heat sources e.g. steam pipes, radiators, hot air ducts, ovens, etc. should be avoided. Product is best stored in original packaging until ready for use.

Safety recommendation:

