

Audurra™ Protective Film green

MASKING

Description:

Good cutting ability and adhesion of the Audurra™ Protective Film green (light-green transparent) accelerate the work steps and are a prerequisite for safe and accurate covering. Universally applicable self-adhesive protective film designed to provide temporary surface protection during manufacturing, transport, storage, or installation.



Features:

- Self-adhesive
- Extremely tear-resistant & universally applicable
- Strongly adhesive and easy to remove
- Color: Green-transparent

Areas of application:

- For sealing windows with defective or missing panes
- As door trim when replacing windows
- Entry protection for door sills ... and many more

Available in:

Article number	Description	Dimension
D15419786	Audurra™ Protective Film green	0,6 x 100m
D15419787	Audurra™ Protective Film green	0,9 x 100m

Compatible with:

Article number	Article description	Packaging unit
D15352432	Audurra Foil Cutter	1 bundle = 5 pieces
D15419691	Audurra Magnetic Foil Cutter	1 bundle = 5 pieces

Audurra™ Protective Film green

MASKING

Properties:

Property	Value & measuring unit	Measuring method
Density	0,925 g/cm ³ (+/- 10%)	Following DIN EN 1183
Thickness	80 µm (+/- 10%)	Following GPA (Thickness-profile)
Tensile strength <i>machine direction</i>	30 N/mm ² (+/- 10%)	Following ASTM D 882
Tensile strength <i>transverse direction</i>	25 N/mm ² (+/- 10%)	Following ASTM D 882
Elongation at break <i>machine direction</i>	300 % (+/- 10%)	Following ASTM D 882
Elongation at break <i>transverse direction</i>	550 % (+/- 10%)	Following ASTM D 882
Adhesion value	20-22 N/5cm (stainless steel)	2 – 5 minutes after application

Conditions of use:

The surface must be clean, dry and free of grease. Film must be laminated without wrinkles and bubbles (roller lamination). The ambient temperature when removing the film should be between + 5 °C and + 50 °C, in frost the film must not be removed. In any case, the user must test the suitability of the film with regard to thermal and mechanical stress and the duration of use, as we can only give recommendations for the large number of possible applications. These are non-binding and in any case exclude liability for damages and disadvantages of any kind, including with regard to the property rights of third parties.

Audurra™ Protective Film green

MASKING

Storage remarks:

Storage time: max. 3 months with no loss of adhesive. Keep storage temperature at + 20° C / $\pm 10^{\circ}$ C and the relative humidity between 30 – 90%. Storage in closed rooms.

This technical information has been given to the best of our knowledge. The above mentioned standards are average values and no granted assurance of special properties. This statement is limited to the material, in the state as it leaves the manufacturer and does not include possible modifications by conversion and/or handling after dispatch.

