

Audurra™ Single Use Overall**PERSONAL PROTECTION****Description:**

Due to its breathable texture and its red back, which is permeable to air, this overall offers the best wearing comfort combined with superior protection against hazardous dusts (Type 5) and certain light liquid splashes (Type 6)

**Features:**

- Elastic belly-band
- Comfortable two-way zipper
- Big-sized elastic knitted arm band
- Functional elastic band at the legs
- Antistatic
- Type 5: EN ISO 13982-1 Protection against damaging dust
- Type 6: EM 13034 Limited protection against liquid chemicals
- Silicon-free



Audurra™ Single Use Overall

PERSONAL PROTECTION

Available in:

Description	Article number	Size	Packaging
Audurra Single-Use Overall	D15352633	S	1 piece
	D15352634	M	1 piece
	D15352635	L	1 piece
	D15352636	XL	1 piece
	D15352637	XXL	1 piece
	D15352638	XXXL	1 piece

Typically applications:

Specially designed for usage in the spray-booth while working with solventbased or waterbased paint (Category III, Type 5/6).



CHEMICAL PROTECTION



EN13982-1:2004
+A1:2010
TYPE 5



EN1149-5:2008



EN13034:2005
+A1:2009
TYPE 6

Audurra™ Single Use Overall

PERSONAL PROTECTION

Performance Profile of Audurra Spraysuit							
Physical data		Test method		Result		Class	
				Front	Back	Front	Back
Abrasion resistance		EN530 method 2		500<cycles<100		3/6	3/6
Seam strength		ISO 13935-2		55.8N-111N-73N-107N-120N		2/6	
Puncture resistance		EN863		11.5N	7N	2/6	1/6
Ignition Resistance		EN 13274-4 method 3		Pass			
Flex cracking		ISO 7854 method B		>100,000 cycles		6/6	6/6
Tensile Strength		ISO 13934-1		112N weft	67N weft	1/6	2/6
				53N warp	89N warp		
Trapezoidal Tear		ISO9073-4		68.8N weft	32.3N weft	2/6	2/6
				27.6N warp	32.2N warp		
Reduced Spray test		EN468(EN13034/05+A1/09) Type 6		Pass			
Whole suit dust test		EN13982-2/04 Type 5		Pass			
Resistance to penetration and repellency by liquid in accordance with EN 6530							
				Repellency		Penetration	
				Front	Back	Front	Back
H ₂ SO ₄ (Sulphuric acid) 30%		EN6530		Class 3/3(95.4%)	Class 2/3(93.6%)	Class 3/3(0%)	Class 3/3(0%)
NaOH(Sodium hydroxide) 10%		EN6530		Class 3/3(97.6%)	Class 3/3(95.8%)	Class 3/3(0%)	Class 3/3(0%)
o-xylene		EN6530		Class 3/3(94.6%)	Class -/3(0.8%)	Class 3/3(0%)	Class -/3(28.8%)
Butan 1 ol		EN6530		Class 3/3(96.7%)	Class -/3(16.9%)	Class 3/3(0%)	Class -/3(26.8%)

Maintenance instruction:



Do not wash



Do not iron



Do not machine dry



Do not dry clean



Inflammable. This garment is expressly constructed as a protection against chemical hazards, and should not, under any circumstances, come into contact with naked flame, or be used in a combustible situation.


Product must never be altered or modified.

Audurra™ Single Use Overall

PERSONAL PROTECTION

Size table:

Body measurement in cms in compliance with 13688:2013					
Size	Chest girth	Body Height	Size	Chest girth	Body Height
S	86-94	158-166	XL	110-118	182-190
M	94-102	166-174	XXL	118-129	190-198
L	102-110	174-182	XXXL	129-141	198-206



An appropriate size garment should be selected to allow for sufficient movement for the task.

Storage and Disposal:

- Store in dry, clean conditions in original packaging
- Store away from direct sunlight, sources of high temperature, and solvent vapors
- Store within the temperature range -20°C to +25°C (-4°F to +68°F) and with relative humidity below 80%
- Replace garments if damaged, heavily contaminated or in accordance with local work practice or regulations
- Handle and dispose of contaminated garments with care and in accordance with national regulations